

ER2DAF

SURFACE MOUNT RECTIFIER

VOLTAGE	200 Volts	CURRENT	2 Amperes
----------------	------------------	----------------	------------------

FEATURES


- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- For surface mounted applications
- Glass passivated junction
- Easy pick and place
- High temperature metallurgically bonden-no compression contacts as found in other diode-constructed rectifiers
- Ultra thin profile package for space constrained utilization
- Package suitable for automated handling
- Lead free in comply with EU RoHS 2011/65/EU directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case: Epoxy molded
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0011 ounces, 0.0328 grams
- Polarity : Color band denotes cathode end



SMAF Unit : inch(mm)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	ER2DAF	UNITS
Recurrent Peak Reverse Voltage	V _{RRM}	200	V
RMS Voltage	V _{RMS}	140	V
DC Blocking Voltage	V _R	200	V
Average Forward Current	I _{F(AV)}	2	A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I _{FSM}	50	A
Forward Voltage at 2.0A	V _F	0.95	V
DC Reverse Current at Rated DC Blocking Voltage T _J =25°C	I _R	1	μA
Reverse Recovery Time (Note 3)	t _{rr}	35	ns
Typical Junction capacitance V _R =4V,1MHz	C _J	30	pF
Typical Thermal Resistance ,Junction to Lead (Note 1) Junction to Ambient (Note 2)	R _{θJL} R _{θJA}	25 150	°C / W
Operating Junction Temperature and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

NOTES :


- 1.Mounted on an FR4 PCB, single-sided copper, with 100cm²copper pad area.
- 2.Mounted on an FR4 PCB, single-sided copper, mini pad.
- 3.Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, Recover to 0.25A.

RATING AND CHARACTERISTIC CURVES



ER2DAF

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 10K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

ER2DAF


Part No_packing code_Version

0ÜG000_R1_00001

0ÜG000_R2_00001

For example :

RB500V-40_R2_00001m



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



ER2DAF

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.